



# Vane anemometer

## testo 410 – Pocket-sized flow velocity measuring instrument

Flow velocity measuring instrument with temperature measurement

Integrated measurement with 40 mm vane

Time mean value calculation

Hold function and max./min. values

Windchill calculation for outdoor areas

Additional advantages testo 410-2: Air humidity measurement with long-term stable Testo humidity sensor



Illustration 1.1

The vane anemometers testo 410-1 and testo 410-2 offer perfect flow velocity measurement results in handy pocket format. The small, user-friendly testo 410-1 measures air flow velocity and temperature, and is suitable for fast spot checks on ventilation outlets thanks to the integrated measurement with the 40 mm vane. A timed mean value calculation is also possible. The measuring instrument has an illuminated display, a clip-on protective cap, and a wrist strap and a belt holder ensure safekeeping.

In addition to air flow velocity and air temperature, the testo 410-2 also measures air humidity. This allows air conditions to be tested reliably. In addition to this, dewpoint and wet bulb are calculated and displayed fully automatically.

# Technical data / Accessories

## testo 410-1

testo 410-1 handy vane anemometer with integrated NTC air thermometer incl. protection cap, batteries and calibration protocol

Part no. 0560 4101



### General technical data

Dimensions	133 x 46 x 25 mm (incl. protective cap)
Operating temperature	-10 to +50 °C
Storage temperature	-20 to +70 °C
Protection class	IP10
Battery type	2 AAA micro batteries
Weight	110 g (with protective cap and batteries)
Measuring rate	0.5 s
Warranty	2 years

## testo 410-2

testo 410-2 handy vane probe anemometer with integrated humidity measurement and NTC-air thermometer incl. protection cap, batteries and calibration protocol

Part no. 0560 4102



0981 9744/msp/A/06.2013

### Technical data

### testo 410-1/-2

### testo 410-2

<b>Sensor types</b>	<b>Vane</b>	<b>NTC</b>	<b>Testo humid. sensor, cap.</b>
Meas. range	0.4 to 20 m/s	-10 to +50 °C	0 to 100 %RH
Accuracy ±1 digit	±(0.2 m/s + 2% of mv)	±0.5 °C	±2.5 %RH (5 to 95 %RH)
Resolution	0.1 m/s	0.1 °C	±0.1 %RH
Battery life	100 h (average, without display illumination)		60 h (average, without display illumination)

Subject to change without notice.

### Accessories

### Part no.

#### Accessories for measuring instrument

ISO calibration certificate velocity two point calibration; calibration points 5m/s and 10m/s	0520 0094	
ISO calibration certificate velocity hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034	

### Testo India Pvt Ltd

#### Head Office:

Plot No. 23, Sindh Society, Baner Road,  
Aundh, Pune - 411007, Maharashtra, India  
Tel: +91 20 6560 0203 | Fax: +91 20 2585 0080  
Email: info@testoindia.com | Web: www.testo.in

#### Regional Offices / Representatives:

Ahmedabad | Baroda | Bengaluru | Chandigarh | Chennai | Guwahati  
Hyderabad | Indore | Kolkata | Mumbai | New Delhi | Raipur

### Authorized Channel Partner

#### Sunshine Instruments

83. Chinnys Chamber, Dr. nanjappa Road,  
Coimbatore - 641018 Ph -+91 9360023357  
E mail - instrumentsindia2012@gmail.com

Branch Off - Mumbai - 400 002