

# NEW DV3T™ Rheometer

the all-in-one tool for measuring viscosity and yield stress



## What's Included?

Instrument  
6 spindles (RV/HA/HB)  
or 4 spindles (LV)  
PG Flash Software ▶  
RTD Temperature Probe  
Spindle Guard Leg\*  
Lab Stand (Model G)  
Convenience Pack  
(USB Flash Drive, Stylus, Cleaning Cloth)  
Carrying Case  
\*Not applicable to HA or HB torque models

### 7-inch Full Color Touch Screen Display

- New User Interface
- Enhanced Controls
- Real Time Graphing
- Supports Multiple Languages

### Displayed Info:

- Viscosity (cP or mPa•s)
- Temperature (°C or °F)
- Shear Rate/Stress
- % Torque
- Speed/Spindle
- Step Program Status
- Math Model Calculations

**Built-in math models** for data analysis in stand-alone mode. E.g. Casson, Bingham, Power Law, Thix Index

### Enhanced Security

- Customizable User Access
- Date and Time Stamp File
- Password Access
- Portable Log-in Settings

### Built-In Options

- Math Modeling
- Temperature Control
- Yield Tests
- Programmable QC Limits/Alarms

**Analyze characteristics** such as yield stress, flow curves (mixing, pumping, spraying), leveling and recovery

**USB PC Interface** provides optional computer control and automatic data collection capability

### Convenient Bubble Level

**Integrated Temperature Control** with connection to Brookfield TC series Baths and AP controller or Brookfield Thermosel System.

**Stand-alone programming** or download custom test programs with PG Flash Software.

### Built-in RTD Temperature Probe

- Accuracy: ±1.0% of range**
- Displayed with test data

### Repeatability: ±0.2%

MODEL	VISCOSITY RANGE cP(mPa•S)		SPEEDS	
	Min.	Max.	RPM	Number of increments
DV3TLV	1†	6M	.01-250	2.6K
DV3TRV	100††	40M	.01-250	2.6K
DV3THA	200††	80M	.01-250	2.6K
DV3THB	800††	320M	.01-250	2.6K
DV3T5xHB	4k	1.6B	.01-250	2.6K

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.  
†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.  
B = 1 billion M = 1 million K = 1 thousand cP = Centipoise mPa•s = Millipascal•seconds

# Introducing new touch screens

## PG Flash Software Included

PROGRAM GENERATOR SOFTWARE FOR CUSTOMIZING TEST CRITERIA FOR ROUTINE PRODUCT QC

This exclusive Brookfield software allows you to create repeatable custom tests on your PC!

Once the program (up to 25 steps) is created, it can be downloaded to a supplied USB flash drive and then uploaded to any DV3T Viscometer.



PG Flash allows users to create repeatable custom tests with all of the built-in options on the DV3T plus the addition of multiple program lines (up to 25 steps). Create the program on the PC and download to a USB Flash Drive. Upload the program from the USB Flash Drive to the DV3T.

## RheocalcT Software Optional

GET TOTAL CONTROL OF YOUR INSTRUMENT AND TEST PARAMETERS

Automatically control and collect data with RheocalcT and a dedicated computer.

RheocalcT can analyze data, generate multiple plot overlays, print tabular data, run math models and perform other time-saving routines. Up to five comparison data sets can be plotted and saved. Other features include:

- Wizards to guide you through the creation of common tests
- Secure 21CFR features including multiple logins, access levels, digital signatures, and data storage in a password-protected database
- Looping functions for repetitive tasks
- Averaging of collected data by step or whole test
- Math models: Bingham, Casson, Casson NCA/CMA, Power Law, IPC Paste, Herschel-Bulkley, Thix Index



### Advanced Application Labo

ANM House,  
Plot No. A-141, Road No. 23,  
Wagle Industrial Area,  
Thane (W) 400 604. INDIA

Tel.: 91-22 - 6614 1666  
Fax: 91-22 - 6614 1678  
Email: info@brkindia.net  
URL: www.brkindia.net



### DV3TCP

The DV3T is available in a Wells/Brookfield Cone & Plate Version  
Must be ordered when instrument is first purchased.



### DV3T with Optional Vane Spindles

DV3T Rheometers have a built-in yield stress measurement capability that determines the stress required to initiate flow of slow moving or paste materials. Vane spindles can be immersed into a material without destroying the underlying structures that contribute to yield. The DV3T offers test parameters that create a specific yield test protocol that can be utilized for QC testing or research.

### DV3T Extra

Includes our ball bearing suspension system, EZ-Lock Spindle Coupling System and FREE RheocalcT software.

Authorised Distributor / Dealer



SUNSHINE INSTRUMENTS  
83, CHINNY'S CHAMBER, DR. NANJAPPA ROAD  
COIMBATORE - 641 018 TAMIL NADU INDIA  
Ph - +91 422 239 3357 / +91 93600 23357  
E mail - instrumentsindia2012@gmail.com

on-line powder rheology texture viscosity