



Pen type, separate ORP electrode, IP-65

ORP METER

Model : ORP-213

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC



The Art of Measurement

Pen type, separate ORP electrode, IP 65



ORP METER

Model : ORP-213

FEATURES	
* Use for ORP (Oxidation Reduction Potential) measurement in plating baths, waste water monitoring and other applications such as Aquarium, Beverage, Fish hatcheries, Food processing, Photography, Laboratory, Quality control, School & Colleges, Swimming Pools....	
* Professional pen digital type ORP meter.	
* Range : -1,000 mV to 1,000 mV.	
* IP 65 water resistance, heavy duty.	
* Complete set with ORP electrode, ORP-14.	
* Separate ORP electrode, easy for general purpose usage and remote measurement.	
* Build in reverse display button.	
* Data hold.	
* Auto power off.	
* Compact size, light weight.	

SPECIFICATIONS		
Display	LCD, size : 20 mm x 28 mm. * User can reverse the display direction by push button.	
Measurement	ORP (Oxidation Reduction Potential).	
Range	-1,000 mV to +1,000 mV.	
Resolution	1 mV.	
Accuracy	± (0.8 % + 1 d) * Main instrument .	
Input Impedance	10 ¹² ohms.	
Sampling Time	Approx. 0.8 second.	
Operating Temp.	0°C to 50°C (32°F to 122°F)	
Operating Humidity	Less than 80% RH.	
Power Supply	DC 1.5V battery (UM-4/AAA) x 4 PCs.	
Power Consumption	Approx. 4.8 mA.	
ORP Electrode	Any ORP Electrode with BNC connector.	
Dimension	Meter	180 x 40 x 40 mm (7.1 x 1.6 x 1.6 inch)
	Electrode	12.5 mm Dia, x 150 mm, * Cable length : Approx. 3 meters.
Weight	Meter	190 g/0.42 LB
	Electrode	88 g/0.2 LB.
Standard Accessories	Instruction Manual..... 1 PC	
	ORP electrode, ORP-14..... 1 PC * ORP-14 is the consumer accessory.	
Optional Accessories	* Soft carrying case with sash (210 x 80 x 50 mm), Model : CA-52A	
	* Hard carrying case (280 x 195 x 65 mm), Model : CA-06	

* Appearance and specifications listed in this brochure are subject to change without notice.

0705-ORP213