



Eutech 5+ & 6+ Series Economy Handheld

- pH • ORP • Ion • Conductivity • TDS • Salinity • Dissolved Oxygen

SOLUTIONS FOR WATER ANALYSIS

EUTECH
INSTRUMENTS
Technology Made Easy ...





Corporate Profile

EUTECH
INSTRUMENTS
Technology Made Easy ...

| Over 15 Years of Product Excellence | Eutech Instruments is a leading ISO9001-certified company established in 1990. Dedicated to the design and manufacture of sensor-based instruments for water quality analysis, Eutech is a pioneer in the development of ASIC-based (Application Specific Integrated Circuit) instruments, and is internationally recognised for its achievements in sensor technology, software programming and product design. Eutech has an extensive product line, which includes the world's first Windows® CE-driven colour touchscreen research-grade bench meter.

| Commitment to R&D | Eutech's competitiveness comes from our strong commitment to R&D. This is backed by a dedicated team of scientists and engineers that thrives on meeting new technological challenges to simplify laboratory and field analytical procedures. The Eutech team is constantly driven to explore the latest technologies and applying them in our design and manufacture of advanced instruments. The result is a line of products that are accurate, consistent, reliable and easy to use.

| Comprehensive Product Line | Eutech's constant drive for innovation is reason for our unique and expansive portfolio of microprocessor-based instruments and chemical sensor systems. We offer a comprehensive range of laboratory and field instruments for electrochemical and photometric water analysis. Eutech also manufactures continuous on-line process instruments for the monitoring and control of pH, Conductivity, Total Dissolved Solids (TDS), Redox Potential (ORP), Dissolved Oxygen (DO) and other water quality parameters.

Eutech products range from compact pocket testers and portable meters to research-grade benchtop meters and industrial process controllers. Each product carries the signature Eutech intuitive design and is packed with advanced user-friendly features.

| Customer Focus | Every Eutech innovation is conceptualised with the user in mind. This, coupled with our strategic location in the design and technology hub of Asia, has enabled the company to produce cutting edge instruments at competitive prices. Our consistent demonstration of insight into customer needs and product demands has earned the company consecutive Frost & Sullivan Market Engineering awards for Product Line Strategy.

Driven by a successful Total Customer Satisfaction Program incorporated in the ISO9001:2000 Quality System, all products undergo extensive testing and calibration by a qualified team of technical experts. Stringent quality control measures guarantee consistency, durability and performance. Eutech products are certified to comply with various global testing standards.

| Forging New Frontiers in Water Analysis | Underlying Eutech's objective to be a world leader in the field of water analysis instrumentation, the company adopts a proactive stand in anticipating the needs of the industry. With increasing global awareness and concern for water quality, the future provides new and exciting challenges and opportunities. To realize the potential of advanced water analytical technologies, Eutech will continue to forge close links and strategic alliances with research institutions, government agencies and private sector firms worldwide. These efforts support the Eutech mission – to make advanced technology easy to use.

| Global Reach | Eutech products are marketed in over seventy countries

worldwide, through an extensive network of associate companies and distributors, with manufacturing facilities in Singapore and Malaysia. Eutech Instruments Singapore has a full-fledged value-chain operation which comprises R&D, manufacturing, marketing, customer service and logistics for worldwide support to customers.

| Thermo Fisher Scientific | Eutech is part of Thermo Fisher Scientific, the world leader in serving science. Thermo Fisher Scientific enables customers to make the world healthier, cleaner and safer by providing analytical instruments, equipment, reagents and consumables, software and services for research, analysis, discovery and diagnostics. With annual sales of more than \$9 billion, Thermo Fisher Scientific has 30,000 employees and serves more than 350,000 customers in

pharmaceutical and biotech companies, hospitals and clinical diagnostic labs, universities, research institutions and government agencies as well as environmental, industrial quality and process control settings.

Global Offices

Asia Pacific (Head Office) | Eutech Instruments Pte Ltd
Blk 55, Ayer Rajah Crescent, #04-16/24, Singapore 139949
Tel: (65) 6778-6876 • Fax: (65) 6773-0836 • www.eutechinst.com

North & South America | OAKTON Instruments
P.O. Box 5136, Vernon Hills, IL 60061, USA
Tel: toll free 1-888-4OAKTON (1-888-462-5866)
• Fax: (1) 847-247-2984 • www.4oakton.com

Europe | Eutech Instruments Europe B.V.
P.O. Box 254, 3860 AG Nijkerk Netherlands Wallerstraat 125K, 3862 CN Nijkerk Netherlands
Tel: (31) 033-2463887 • Fax: (31) 033-2460832 • www.eutech.nl

Malaysia | Eutech Instruments Sdn Bhd
No. 1, Lengkok Keluli 2, Bukit Raja Prime Industrial Park, 41050 Bukit Raja, Klang Selangor D.E., Malaysia
Tel: (603) 3342-8533 • Fax: (603) 3342-6520 • www.eutechinst.com

China | Thermo Fisher Scientific
Building 6, No. 27, Xin Jinqiao Road, Shanghai 201206, China
Tel: (86) 21-6865-4588 • Fax (86) 21-6445-7909 • www.eutech.cn

India | Thermo Fisher Scientific
102, 104, Delphi 'C' Wing, Hiranandani Business Park, Powai Mumbai - 400 076, India
Tel: (91) 22-6742-9494 • Fax: (91) 22-6742-9495 • www.eutechinst.com



Contents

Main Features	>> 04
Eutech Ion 6+; pH 6+ & pH 5+	>> 05
Eutech COND 6+, TDS 6+ & Salt 6+	>> 06
Eutech DO 6+	>> 07
Accessories	>> 08
Ordering Information	>> 09
Specification Tables	>> 10



Main Features

- Easy To Use
- Self-Diagnostic
- IP54 Rating
- Convenient Push-Button Calibration
- Energy-Saving & Low Maintenance
- Compact & Lightweight



Rubber Boot protects against knocks and hits



Easy-To-Read Display
Customised LCD screen



Tactile Keypad with simple, straightforward design for easy operation



Compact Design Fits Your Palm Perfectly
Designed for easy single-hand operation



Convenient Benchtop Stand

User-Friendly
Diagnostic, easy to understand trouble-shooting prompts

Splashproof & Shock-Resistant Built with shock-resistant ABS plastic and protected by an IP54-rated housing against accidental splashes

Hold Function
Freezes readings momentarily for easy viewing and recording

Energy and Cost Saving
Switches off automatically after 20 minutes of inactivity

Automatic Temperature Compensation
Accurate readings, even under varying temperature conditions

Non-Volatile Memory
Meter settings are saved, even when batteries run out



Eutech Ion 6+

pH / ORP / Ion / Temperature

The Eutech Ion 6+ is value-for-money, offering measurements for pH, ORP, temperature and ion concentration. With its compact and sturdy design, the lightweight meter is your ideal choice for field and lab work.

- Convenient and easy to use with pre-programmed Ion calibration points
- mV mode allows you to check electrode calibration and performance
- Offers a wide measurement range of up to ± 500 mV
- Compatible with a large variety of ISE electrodes

Applications: • Pools and spas • Ponds and aquariums • Agriculture and hydroponics • Water and wastewater treatment • Cooling towers • Food processing • Photo-development and printing • Ecological studies • Field, laboratory and education institutions

Eutech Ion 6+; pH 6+; pH 5+



Eutech pH 6+; Eutech pH 5+

pH / ORP / Temperature

Eutech's pH 6+ and pH 5+ offer you the greatest value-for-money for your basic pH measurement needs. Rugged and user-friendly, these no-frill meters come with protective IP54 rubber boots for protection against harsh field elements.

- High pH accuracy of ± 0.01
- 3-point push-button calibration with auto-buffer recognition – quick, easy calibration with no mistakes
- Self-diagnostic messages for easy trouble-shooting
- Switch between pH and Temperature readouts easily with the press of a button

Expanded Features of Eutech pH 6+

- Measures ORP in addition to pH and Temperature

Applications: • Pools and spas • Ponds and aquariums • Agriculture and hydroponics • Water and wastewater treatment • Cooling towers • Food processing • Photo-development and printing • Ecological studies • Field, laboratory and education institutions



Eutech COND 6+; Eutech TDS 6+



Conductivity / Temperature ; Total Dissolved Solids / Temperature

Sturdy and economical, the Eutech COND 6+ and Eutech TDS 6+ combine ease-of-use with high performance. The handy meters are IP54 splashproof and come with a conductivity/TDS electrode with automatic temperature compensation function – great for fieldwork and value-for-money!

- Up to 5-point push-button calibration with auto-buffer recognition – quick, easy calibration with no mistakes
- Up to $\pm 1\%$ full scale accuracy
- Selectable automatic/manual temperature compensation
- Eutech COND 6+ features auto-ranging capability for Conductivity measurements
- Eutech TDS 6+ features adjustable TDS factor for direct derivation of values

Applications: • Pools and spas • Ponds and aquariums • Agriculture and hydroponics • Water and wastewater treatment • Cooling towers • Food processing • Photo-development and printing • Ecological studies • Field, laboratory and education institutions

Eutech COND 6+, TDS 6+ & Salt 6+



Eutech Salt 6+

Salinity / Temperature

The lightweight Eutech Salt 6+ offers $\pm 1\%$ full scale accuracy and comes with an electrode designed with in-built automatic temperature compensation function – handy, accurate and very user-friendly.

- Measures in ppt and %
- Temperature readings accurate to 0.1 °C
- Electrode with built-in ATC designed for minimal air bubble entrapment during measurement
- User-customisation for normalisation temperature and temperature coefficient
- Quick and easy push-button calibration
- Non-linear salt curve provide enhanced accuracy

Applications: • Pools and spas • Ponds and aquariums (marine fish) • Agriculture and hydroponics • Brines • Food processing and healthcare industry • Ecological studies • Field, laboratory and education institutions

Eutech DO 6+



Eutech DO 6+


Dissolved Oxygen / Temperature

Eutech's DO 6+ offers high performance at an affordable price. Rugged and user-friendly, this no-frills meter comes in a sturdy IP54-rated housing, and measures in both mg/L (ppm) and % saturation.

- Push-button calibration with auto-buffer recognition for quick and easy calibration with no mistakes
- Calibration can be performed at 100 % and/or at 0 % against a known solution
- Auto-compensation of Salinity and Barometric Pressure with manual input
- Galvanic probe eliminates polarisation delay and delivers quick, stable response – no warm-up time required!

Applications: • Ponds and aquariums • Aquaculture (catfish and shrimp farming) • Water and wastewater treatment • Recirculating systems • Industrial process systems • Water-quality testing • Surface and ground water testing (meet EPA regulations) • Ecological studies and monitoring • Field, laboratory and education institutions

<< Printing



<< Swimming Pool



<< Aquarium



Eutech Economy Handheld Accessories

| Cyberkit | The Cyberkit consists of a carry case made of sturdy reinforced plastic, calibrating sachets and sample bottles thoughtfully designed to hold your meter and electrodes. It's all you need for your outfield measurements.

| Electrodes | Eutech offers an extensive selection of epoxy and glass-body electrodes for a wide range of parameters and applications. Combination designs are convenient and require no separate sensing and reference half-cell electrodes.

| Buffer & Calibration Solutions (480 ml) | Eutech Buffers and Calibration Solutions are available

in packs of 480 ml durable plastic bottles – economical and convenient for laboratory use. (MSDS and COA can be downloaded under “Support” at <http://www.eutechinst.com>)

| Calibration Sachets (20 x 20 ml Per Box) | Economical NIST traceable sachets offer quick, accurate and convenient calibration. Simply insert electrode into sachet pack, calibrate, rinse and discard sachet – no separate container needed!



Electrodes



pH Buffer Solutions



pH Buffer Sachets



Cyberkit



Economy Handheld Ordering Information



Meters

Model	Order Code	Part No.	Description
Ion	ECION602PLUSK	01X256410	Eutech Ion 6+ Ion/pH/mV Meter with Single Junction pH Electrode ECFC7252101B, ATC Electrode ECPH5TEM01P & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
Ion	ECION601PLUS	01X256409	Eutech Ion 6+ Ion/pH/mV Meter with ATC Electrode ECPH5TEM01P
pH	ECPH603PLUSK	01X245027	Eutech pH 6+ pH/mV Meter with "3-in-1" pH/Temperature Combi Electrode ECFC7352901B & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
pH	ECPH602PLUSK	01X245026	Eutech pH 6+ pH/mV Meter with Single Junction pH Electrode ECFC7252101B, ATC Electrode ECPH5TEM01P & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
pH	ECPH601PLUSK	01X245028	Eutech pH 6+ pH/mV Meter with ATC Electrode ECPH5TEM01P & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
pH	ECPH601PLUS	01X245025	Eutech pH 6+ pH/mV Meter with ATC Electrode ECPH5TEM01P
pH	ECPH503PLUSK	01X244913	Eutech pH 5+ pH Meter with "3-in-1" pH/Temperature Combi Electrode ECFC7352901B & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
pH	ECPH502PLUSK	01X244912	Eutech pH 5+ pH Meter with Single Junction pH Electrode ECFC7252101B, ATC Electrode ECPH5TEM01P & pH Carrying Kit Set (Includes 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each))
pH	ECPH501PLUS	01X244911	Eutech pH 5+ pH Meter with ATC Electrode ECPH5TEM01P
COND	ECCON603PLUSK	01X289425	Eutech COND 6+ Conductivity Meter with Electrode ECCONSEN91B & Conductivity Carrying Kit Set (Includes 1 x 1413 µS, 12.88 mS, 84 µS KCL Standard Solutions & 1 x Deionised (Rinse) Water (60 ml Each))
COND	ECCON603PLUS	01X289426	Eutech COND 6+ Conductivity Meter with Electrode ECCONSEN91B
TDS	ECTDS603PLUSK	01X289427	Eutech TDS 6+ TDS Meter with Electrode ECCONSEN91B & TDS Carrying Kit Set (Includes 1 x 3000 ppm, 300 ppm, 50 ppm 442 Standard Solutions & 1 x Deionised (Rinse) Water (60 ml Each))
TDS	ECTDS603PLUS	01X289428	Eutech TDS 6+ TDS Meter with Electrode ECCONSEN91B
Salt	ECSALT603PLUSK	01X289429	Eutech SALT 6+ Salinity Meter with Electrode ECCONSEN91B & Salinity Carrying Kit Set (1 x 5 ppt, 25 ppt, 45 ppt NaCl Standard Solutions & 1 x Deionised (Rinse) Water (60 ml Each))
Salt	ECSALT603PLUS	01X289430	Eutech SALT 6+ Salinity Meter with Electrode ECCONSEN91B
DO	ECDO602PLUSK	01X370113	Eutech DO 6+ Dissolved Oxygen Meter with 3 m Cable Electrode ECDO6HANDY3M, 2 Assembled Membrane Cap Housing, 1 Refilling Electrolyte (10 ml) & Carrying Kit Set
DO	ECDO601PLUSK	01X370114	Eutech DO 6+ Dissolved Oxygen Meter with 1 m Cable Electrode ECDO6HANDY, 2 Assembled Membrane Cap Housing, 1 Refilling Electrolyte (10 ml) & Carrying Kit Set

Electrodes & Accessories

Model	Order Code	Part No.	Description
pH	ECFC7252101B	01X099412	General Purpose Plastic-Body Single Junction Gel-Filled pH Combination Electrode, 12x110 mm, BNC Connector, 1 m Cable
pH	ECFC7252201B	01X099417	General Purpose Plastic-Body Double Junction Gel-Filled pH Combination Electrode, 12x110 mm, BNC Connector, 1 m Cable
pH	ECFC72522R01B	01X099414	General Purpose Plastic-Body Double Junction Refillable pH Combination Electrode, 12x90 mm, BNC Connector, 1 m Cable & 10 ml Refilling Electrolyte
pH	ECFC7352901B	01X218964	General Purpose Plastic-Body "3-In-1" pH/Temp Combination Electrode, 12x90 mm, BNC Connector, 1 m Cable
pH	ECPH5TEM01P	01X021804	ATC Electrode; 1 m Cable
pH	ECECOPHKIT	01X266901	Economy pH Carrying Kit Set – Plastic Carrying Case Comprises: 1 x pH 4.01, pH 7.00 Buffer Solutions, Storage Solution & 1 x Deionised (Rinse) Water (60 ml Each)
COND	ECCONSEN91B	01X244701	2 Stainless Steel Rings Ultem-Body Electrode with ATC, Cell Constant K=1.0, TDS/Salt 12x110 mm, BNC Connector, 1 m Cable
COND	ECECOCONKIT	01X266902	Economy Conductivity/TDS Carrying Kit Set – Plastic Carrying Case Comprises: 1 x 1413 µS, TDS/Salt 12.88 mS KCl & 3000 ppm 442 Standard Solutions & 1 x Deionised Rinse Water (60 ml)
DO	ECDO6HANDY3M	01X233916	Galvanic Dissolved Oxygen Electrode with ATC, 3 m Cable
DO	ECDO6HANDY	01X233913	Galvanic Dissolved Oxygen Electrode with ATC, 1 m Cable
DO	01X241608	01X241608	Assembled Membrane Cap Housing for ECDO6HANDY & ECDO6HANDY3M
Others	ECECODRYKIT	01X266903	Economy Neutral Carrying Kit Set – Plastic Carrying Case Comprises: 4 x Empty Sample Bottles (60 ml)




Economy Handheld Specification Tables





| Warranty | Eutech Instruments provides three years of warranty against manufacturing defects for our meters, and six months for our electrodes.




Eutech reserves the right to make changes, improvements and modifications to products shown.

pH/Oxidation Reduction Potential (ORP) Economy Handheld Meters		Ion 6+	pH 6+	pH 5+
				
pH	Range	0.00 to 14.00 pH		
	Resolution	0.01 pH		
	Accuracy	±0.01 pH		
	Calibration Points	Up to 3		
	Buffer Sets	USA, NIST, PWB		
Ion	Range	0.01 to 0.99, 1.0 to 199.9, 200 to 1999 ppm	-	
	Resolution	0.01, 0.1, 1 ppm	-	
	Accuracy	±1 % full scale	-	
	Calibration Points	Up to 3	-	
Temperature	Range	0.0 to 100.0 °C		
	Resolution	0.1 °C		
	Accuracy	±0.5 °C		
ORP	Range	±500 mV	±1000 mV	-
	Resolution	0.1 mV (±199.9); 1 mV (beyond)	1 mV	-
	Accuracy	±0.2 mV (±199.9); ±2 mV (beyond)	±2 mV	-
Meter Features	Temperature Compensation	ATC/MTC (0 °C to 100 °C)		
	IP Rating	IP54		
	Hold Function	Yes		
	Auto - Off	20 mins after last key press		
	Average/Stability	Yes		
	Inputs	BNC, 2.5 mm phono socket		
	Power Requirements	4x 1.5 V 'AAA' alkaline batteries ; >200 hours		
	Meter	15.7 x 8.5 x 4.2 cm ; 255 g		
Dimensions (LxWxH); Weight	Boxed	24 x 17 x 8 cm ; 555 g		

Conductivity/Total Dissolved Solids (TDS) Economy Handheld Meters		COND 6+	TDS 6+
			
Conductivity	Range	.. to19.99 µS/cm, 19.9 µS/cm to 199.9 µS/cm, 199 µS/cm to 1999 µS/cm, - 2.00 mS/cm to 19.99 mS/cm, 20.0 mS/cm to 199.9 mS/cm	
	Resolution	0.05 % full scale-	
	Accuracy	±1 % full scale + 1 LSD-	
TDS	Range	.. to 9.99 ppm *, 10.0 ppm to 99.9 ppm, 100 ppm to 999 ppm,	
	Resolution	1.00 ppt to 9.99 ppt, 10.0 ppt to 99.9 ppt	
	Accuracy	-0.05 % full scale	
	TDS Factor	-±1 % full scale + 1 LSD	
Calibration Points	-0.40 to 1.0		
Temperature	Range	4 (1 per range) auto, 5 (1 per range) manual5 (1 per range) manual	
	Resolution	0.0 to 80.0 °C / 32 to 176 °F (with supplied probe)	
	Accuracy	0.1 °C / 0.1 °F	
	Coefficient	±0.5 °C / ±0.9 °F	
	Normalisation	0.0 to 3.0 %	
	Operating Range	20.0 or 25.0 °C	
	Cell Constant	0 to 50 °C	
	Temperature Compensation	0.1, 1.0, 10.0	
Meter Features	IP Rating	ATC/MTC (0 °C to 80 °C) (with supplied probe)	
	Hold Function	IP54	
	Auto - Off	Yes	
	Inputs	20 mins after last key press	
	Power Requirements	BNC, 2.5 mm phono socket	
	Meter	4x 1.5 V 'AAA' alkaline batteries ; >100 hours	
	Meter	15.7 x 8.5 x 4.2 cm ; 255 g	
Dimensions (LxWxH); Weight	Boxed	24 x 17 x 8 cm ; 555 g	

* Maximum 199.9 ppt depending on factor setting

Salinity Economy Handheld Meter		Salt 6+	
			
Salinity (TDS)/%	Range	.. to 50.0 ppt / .. to 5.00 %	
	Resolution	0.1 ppt / 0.01 %	
	Accuracy	±1 % full scale	
	Calibration Points	1	
Temperature	Range	-10 to 80 °C	
	Resolution	0.1 °C	
	Accuracy	±0.5 °C	
	Coefficient (Per °C)	0.0 to 3.0 %	
	Normalisation	20.0 °C and 25.0 °C (selectable)	
Meter Features	Temperature Compensation	ATC/MTC (0 to 50 °C)	
	IP Rating	IP54	
	Hold Function	Yes	
	Auto - Off	20 mins after last key press	
	Inputs	BNC, 2.5 mm phono socket	
	Power Requirements	4x 1.5 V 'AAA' alkaline batteries ; >100 hours	
Dimensions (LxWxH); Weight	Meter	15.7 x 8.5 x 4.2 cm ; 255 g	
	Boxed	24 x 17 x 8 cm ; 555 g	

Dissolved Oxygen (DO) Economy Handheld Meter		DO 6+	
			
Dissolved Oxygen	Range	0.00 to 19.99 mg/L or ppm	
	Resolution	0.01 mg/L or ppm	
	Accuracy	±1.5 % full scale	
% Of Saturation Of Oxygen	Range	0.0 to 199.9 %	
	Resolution	0.10 %	
	Accuracy	±1.5 % full scale	
Temperature	Range	0.0 to 50.0 °C / 32 to 122 °F	
	Resolution	0.1 °C	
	Accuracy	±0.5 °C	
Salinity Correction	Range	0.0 to 50.0 ppt	
	Resolution	0.1 ppt	
	Method	Automatic correction after manual input	
Barometric Pressure Correction	Range	500 to 1499 mmHg or 66.6 to 199.9 kPa	
	Resolution	0.1 mmHg or 0.1 kPa	
	Method	Automatic correction after manual input	
Calibration	2-point (0 %, 100 %), 1-point (mg/L)		
Probe	Type	Galvanic	
Meter Features	Temperature Compensation	ATC/MTC (0.0 °C to 50.0 °C)	
	IP Rating	IP54	
	Hold Function	Yes	
	Auto - Off	20 mins after last key press	
	Inputs	BNC, 2.5 mm phono socket	
	Power Requirements	4x 1.5 V 'AAA' alkaline batteries ; >100 hours	
Dimensions (LxWxH); Weight	Meter	15.7 x 8.5 x 4.2 cm ; 255 g	
	Boxed	24 x 17 x 8 cm ; 555 g	





Eutech Instruments manufactures a comprehensive range of laboratory and field instrumentation for water analysis. Eutech Instruments also produces on-line process instruments for water quality monitoring and control. Innovative products from Eutech include:

Dual Display Testers | Economy + Series Handhelds | Waterproof Colorimeters and Turbidimeters | CyberScan Handhelds
CyberScan Bench Meters | CyberScan Touchscreen Meters

| World-Wide Sales and Service Support | Eutech provides

world-wide sales and service support for all its products through its network of international distributors. Contact us at eutech@thermofisher.com for details of your nearest distributor.



**EUTECH
INSTRUMENTS**
Technology Made Easy ...

Part of Thermo Fisher Scientific



SINGAPORE 1000
SINGAPORE SME 500
2006 & 2007

www.eutechinst.com | eutech@thermofisher.com

Singapore • USA • Netherlands • Malaysia • China • India

Distributed by: