

INTRODUCING

MERA PAL UREA



• Wide Urea Range of 0-55% with accuracy of 0.2%



• Extremely water resistant (IP65)
• Can be washed under running water



• Automatic Temperature Compensation (ATC)



• Measurement temperature direct display in °C



• Revolutionary new External Light interference (ELI) feature **Patented**



Measurement Method



1 Apply 2-3 drops on the prism surface.



2 Press the START key.



3 Measurement value and prism temperature are displayed in 3 seconds

Digital Handheld Pocket Refractometer MERA PAL UREA specifications

Cat.#	4694
Measurement range	0.0 to 55.0% UREA (Automatic Temperature Compensation) 10.0 to 40 °C
Resolution	0.1% UREA / 0.1 °C
Accuracy	± 0.2% UREA / 0.1 °C
Automatic temperature compensation range	10 to 40°C
Ambient temperature range	10 to 40°C
Battery life	Approx. 11,000 measurements (when using alkaline batteries)
Dimensions and weight	55(W)x31(D)x109(H)mm, 100g (Main unit only)

All ATAGO products are designed and manufactured in Japan.

HACCP GMP GLP

ATAGO products comply with HACCP, GMP, and GLP system standards.

ATAGO CO., LTD.

Headquarters: The Front Tower Shiba Koen, 23rd Floor
2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan
TEL : 81-3-3431-1943 FAX : 81-3-3431-1945
overseas@atago.net http : //www.atago.net/



ATAGO INDIA Instruments Pvt. Ltd.

Unit # 103, Western Edge II, Opp. Magathane Bus Depot,
Off. Western Express Highway, Borivali (East), MUMBAI – 400 066
customerservice@atago-india.com, Tel. : 022-4071 3232

NEW DELHI - customerservice-del@atago-india.com, Tel. : 011-2205 0093
CHENNAI - customerservice-chn@atago-india.com, Tel. : 044-4042 3171
BENGALURU - customerservice-blr@atago-india.com
HYDERABAD - customerservice-hyd@atago-india.com
AHMEDABAD - customerservice-ahd@atago-india.com

* Specifications and appearance are subject to change without notice.

