



*Acc., Vel., Displacement, data logger*

# VIBRATION METER

Model : VB-8213

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC

*The Art of Measurement*



# VIBRATION METER

Model : VB-8213

## 1. FEATURES

* Applications for industrial vibration monitoring : All industrial machinery vibrates. The level of vibration is a useful guide to machine condition. Poor balance, misalignment & looseness of the structure will cause the vibration level increase, it is a sure sign that the maintenance is needed.
* Frequency range 10 Hz - 1 kHz, sensitivity relative meet ISO 2954.
* Professional vibration meter supply with vibration sensor & magnetic base, full set.
* Metric & Imperial display unit
* Acceleration, Velocity, Displacement measurement.
* RMS, Peak value, Max. hold measurement.
* Wide frequency range.
* Data hold button to freeze the desired reading.
* Memory function to record maximum and minimum reading with recall.
* Separate vibration probe with magnetic base, easy operation.
* RS 232 computer interface.
* Data Logger.
* Optional data acquisition software.
* Optional data logger ( data collection ) software.
* Super large LCD display with bar graph indicator.
* Microcomputer circuit, high performance.
* Auto shut off saves battery life.
* Built-in low battery indicator.
* Heavy duty & compact housing case.
* Complete set with the hard carrying case.

### 2-1 General Specifications

Display	52 mm x 38 mm, LCD display. 16 mm ( 0.63" ) digit size. With bar graph indicator.
Measurement	Velocity, Acceleration, Displacement
Function	<i>Main</i> RMS, Peak, Max. Hold. <i>Others</i> Data hold, Max. & Min. value, Data logger.
Frequency range	10 Hz to 1 KHz * <i>Sensitivity relative during the the frequency range meet ISO 2954 Refer to table 1, page 19.</i>
Circuit	Exclusive microcomputer circuit.
Data hold	Freeze the desired reading.
Peak measurement	To measure the peak value.
Max. hold measurement	To measure and update the max. peak value.
Memory	Maximum & Minimum value.
Power off	Auto shut off, saves battery life, or manual off by push button.
Sampling time	Approx. 1 second.
Sampling Time of Data Logger	0, 1, 2, 10, 30, 60, 600, 1800, 3600 sec. * <i>0 second : Manual data logger.</i> * <i>Other sampling time beyond 0 second : Auto data logger.</i>
Data Logger No.	500 no. max.
Data output	RS 232 serial output, isolate.
Operating temperature	0 to 50 °C ( 32 to 122 °F ).
Operating humidity	Less than 80% RH.
Power supply	Alkaline or heavy duty type, DC 9V battery, 006P, MN1604 (PP3) or equivalent.
Power consumption	Approx. DC 13 mA.
Weight	Meter 230 g/0.50 LB Vibration sensor 38 g/0.09 LB
Dimension	Meter : 180 x 72 x 32 mm ( 7.1 x 2.8 x 1.3 inch ). Vibration sensor probe: Round 19 mm Dia. x 21 mm.

Accessories included	Instruction manual..... 1 PC. Vibration sensor with cable..... 1 PC. Magnetic base..... 1 PC. Carrying Case..... 1 PC.
Optional accessories	* RS232 cable, UPCB-01 * USB cable, USB-01 * Data Acquisition software, SW-U801-WIN * Data Logger software, SW-DL2005.

### 2-2 Electrical Specifications

#### Acceleration ( RMS, Peak, Max Hold )

Unit	m/s <sup>2</sup>
Range	0.5 to 199.9 m/s <sup>2</sup>
Resolution	0.1 m/s <sup>2</sup>
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 m/s <sup>2</sup> ( 160 Hz )
Remark	Acceleration peak range : 1.0 to 199.9 m/s <sup>2</sup>

Unit	G @ 1 G = 9.8 m/s <sup>2</sup>
Range	0.05 to 20.39 G
Resolution	0.01 G
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 m/s <sup>2</sup> ( 160 Hz )
Remark	Acceleration peak range : 1.0 to 199.9 m/s <sup>2</sup>

Unit	ft/s <sup>2</sup>
Range	2 to 656
Resolution	1 ft/s <sup>2</sup>
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 m/s <sup>2</sup> ( 160 Hz )
Remark	Acceleration peak range : 1.0 to 199.9 m/s <sup>2</sup>

#### Velocity ( RMS, Peak, Max Hold )

Unit	mm/s
Range	0.5 to 199.9 mm/s
Resolution	0.1 mm/s
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 mm/s ( 160 Hz )
Remark	Velocity peak range : 1.0 to 199.9 mm/s

Unit	cm/s
Range	0.05 to 19.99 cm/s
Resolution	0.01 cm/s
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 mm/s ( 160 Hz )
Remark	Velocity peak range : 1.0 to 199.9 mm/s

Unit	inch/s
Range	0.02 to 7.87 inch/s
Resolution	0.01 inch/s
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	50 mm/s ( 160 Hz )
Remark	Velocity peak range : 1.0 to 199.9 mm/s

#### Displacement p-p ( RMS, Max Hold )

Unit	mm
Range	1.999 mm
Resolution	0.001 mm
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	0.141 mm ( 160 Hz )

Unit	inch
Range	0.078 inch
Resolution	0.001 inch
Accuracy	± ( 5 % + 2 d ) reading @ 160 Hz, 80 Hz, 23 ± 5 °C
Calibration Point	0.141 mm ( 160 Hz )
* Remark :	p-p = Peak to Peak