

all in one, bar graph LED + LCD



MOISTURE METER

Model : MS-7003

9001, CE, EC1010



FEATURES

- *Wood and concrete moisture measurement..
- *Wood material : 0 % to 40 % moisture content.
- *Concrete material : 0 % to 100% moisture content.
- *Red LED bar graph indicator with LCD display,
- *Meter build in test probe, all in one, easy operation.
- *Data hold, Record(max., min.).
- *LCD display with the red LED bar graph.
- *DC 9V battery (006P).



LUTRON ELECTRONIC



The Art of Measurement

Concrete/Wood, Red LED bar graph + LCD display



MOISTURE METER

Model : MS-7003

FEATURES

* Designed to check the moisture level of wood, concrete, and other non-wood material.
* 6 % to 40 % moisture range on wood.
* 0 to 100% relative moisture value for Concrete and other non-wood material.
* Red LED bar graph indicator and LCD digital display.
* All in one, meter build in the test pins.
* Optional separate probe, available for remote measurement.
* Microprocessor circuit assures maximum possible accuracy, provides special functions and features.
* Records Maximum & Minimum reading with recall.
* Data hold function to freeze the desired value on display.
* Heavy duty & compact housing case, designed for easy carry out & operation.
* Built-in low battery indicator.

Material/ Range	Material 1 : 0 to 100% relative moisture value for Concrete. and other non-wood material. Material 2 : 6 % to 40 % moisture range on wood.
Resolution	0.1 %.
Accuracy	$\pm(5 \% + 5 d)$ $@ 23 \pm 5 ?$ $@ Material 1 : 13 \% to 100\%$ $@ Material 2 : 6 \% to 40\%$
Probe	2 pins moisture electrode.
Data Hold	By push button on front panel.
Memory Recall	Records Maximum & Minimum reading value.
Sampling Time	Approx. 0.8 second.
Operating	0 to 50 ? (32 to 122 ?).
Temp./Humidity	Less than 80 %RH.
Power Supply	Alkaline 006P, MN1604 (PP3) DC 9V battery.
Power Current	Approx. DC 16 mA.
Weight	251 g/0.55 LB.
Dimension	216.5 x 68.5 x 29.7 mm (8.4 x 2.7 x 1.2 inch).
Accessories	Instruction manual.....1 PC.
Included	Extra contact pins.....10 PCs.
Optional	Separate Probe, MP-31
Accessories	Hard Carrying Case, CA-06 Soft Carrying Case, CA-05A

SPECIFICATIONS

Applications	Designed to check the moisture level of wood, concrete and other non-wood material.
Principal	Used the 2 pins electrode to measure the conductive ability of the species, then converter to the reading of % " Moisture of Content ".
Circuit	Custom one-chip of microprocessor LSI circuit.
Display	LCD size : 51 mm x 37 mm Digit size : 16 mm (0.62 ")

* Appearance and specifications listed in this brochure are subject to change without notice.

0601-MS7003