

# CL-2054



## Features:

- 3 $\frac{3}{4}$  Digit Manual Range
- 3,999 Count
- 10uA high Resolution
- Auto Power Off (APO)
- Shielded Transformer Jaw Open to 1.2"

### AC VOLTAGE

Range	Resolution	Accuracy	
		50/60 Hz	40-1KHz
400V	0.1V	$\pm 1.5\%$ of rdg $\pm 2$ digits	$\pm 2.0\%$ of rdg $\pm 4$ digits

### AC CURRENT

Range	Resolution	Accuracy	
		50/60 Hz	Wide (400-1KHz)
40mA	10 $\mu$ A	$\pm 1.0\%$ of rdg $\pm 0.5$ mA digits	$\pm 4.5\%$ of rdg $\pm 0.5$ mA digits
400mA	100 $\mu$ A	$\pm 3.0\%$ of rdg $\pm 5.0$ mA digits	$\pm 3.0\%$ of rdg $\pm 5.0$ mA digits
4A	1mA	$\pm 4.0\%$ of rdg $\pm 0.1$ A digits	$\pm 4.0\%$ of rdg $\pm 0.1$ A digits
40A	10mA	$\pm 4.0\%$ of rdg $\pm 1.0$ A digits	$\pm 4.0\%$ of rdg $\pm 1.0$ A digits
80A	100mA	$\pm 2.5\%$ of rdg $\pm 1.0$ A digits	$\pm 3.0\%$ of rdg $\pm 1.5$ A digits
80-100A		$\pm 5.0\%$ of rdg $\pm 1.0$ A digits	$\pm 5.0\%$ of rdg $\pm 1.5$ A digits

### RESISTANCE

Range	Resolution	Accuracy
40-400 $\Omega$	0.1 $\Omega$	$\pm 1.0\%$ of rdg $\pm 2$ digits

CONTINUITY TEST Threshold 40 $\Omega$ , Continuity Beeper 2.5KHz

POWER 9V (6F22) X 1

- Standard Accessories : Hard Carrying Case, Test Lead, Manual
- Dimension : 209(H) x 43(W) x 30(D)mm