

Features:

- 3^{3/4} Digit Clamp Meter with Backlight
- 4000 Count
- Clamp Torch
- Jaw Open : 52mm
- Non Contact Voltage (NCV)
- Duty Cycle : 1-99%
- Frequency / Temperature
- Auto Power Off (APO)

CM-2056



DC VOLTAGE

Range	Resolution	Accuracy
400mV	0.1mV	±1.0% of rdg + 5 digits
4V	1mV	±0.5% of rdg + 5 digits
40V	10mV	
400V	100mV	
1000V	1V	

DC CURRENT

Range	Resolution	Accuracy
400A	100mA	±2.0% of rdg + 5 digits
1000A	1A	>800A: ±4.0% of rdg + 10 digits

AC VOLTAGE

Range	Resolution	Accuracy
400mV	0.1mV	± 1.5% of rdg + 5 digits
4V	1mV	
40V	10mV	
400V	100mV	
750V	1V	± 1.0% of rdg + 5 digits

AC CURRENT

Range	Resolution	Accuracy
400A	100mA	±2.0% of rdg + 5 digits
1000A	1A	>800A: ±4.0% of rdg + 10 digits

RESISTANCE

Range	Resolution	Accuracy
400Ω	0.1Ω	±0.8% of rdg + 5 digits
4kΩ	1Ω	±0.8% of rdg + 3 digits
40kΩ	10Ω	
400kΩ	100Ω	
4MΩ	1KΩ	
40MΩ	10KΩ	±1.2% of rdg + 5 digits

CAPACITANCE

Range	Resolution	Accuracy
4nF	1pF	±5.0% of rdg + 20 digits
40nF	10pF	±3.5% of rdg + 10 digits
400nF	100pF	
4nF	1nF	
4μF	10nF	
40μF	100nF	±5.0% of rdg + 10 digits

FREQUENCY

Range	Resolution	Accuracy
100Hz	0.1Hz	±5.0% of rdg + 20 digits
1kHz	0.1Hz	±3.5% of rdg + 10 digits
10kHz	1Hz	
100kHz	10Hz	
1MHz	100Hz	
10MHz	1kHz	±5.0% of rdg + 10 digits

TEMPERATURE

Range	Resolution	Accuracy
(-40~750)°C	1°C	<400°C ±1.0% of rdg + 5 digits ≥400°C ±1.5% of rdg + 15 digits

POWER 9V (6F22) X 1

- Standard Accessories : Soft Carrying Case, Manual, TP-04 Temperature Probe, Test Lead
- Dimension : 225(H) x 77(W) x 45(D)mm